



Datasheet for part number MDM-51SR074K-F300

| |
|--|
| Our Catalog Part Number: MDM-51SR074K-F300 |
| Our Global Manufacturing Part Number: 096523-2088 |
| Brand: Cannon Product Category: Micro Product Line: Micros Series: MICRO |

| Product Datasheet | |
|---------------------------------|--|
| Series | Micro "D" Metal Shell |
| Arrangement | 51 Contact |
| Gender | Socket |
| Contact Material | Gold plated copper alloy |
| Contact Type | Crimp |
| Contact Resistance | 8 milliohms max. |
| Termination Type | 18" Min, M22759/87 #26AWG, System 1 |
| Shell Material | Stainless Steel |
| Shell Finish | Passivated Stainless Steel |
| Insulator Material | Liquid crystalline polymer |
| Hardware | Jackscrew (standard) |
| Coupling | Jackscrew Coupling |
| Current Rating | 3 A max. |
| Dielectric Withstanding Voltage | 600 VAC at sea level 150 VAC at 70,00' altitude |
| Insulator Resistance | 5000 megohms min. |
| Thermal Shock | -55°C to +230°C |
| Physical Shock | 50 G's, 3 axes, 6 milisecond duration sawtooth pulse |
| Vibration | 20G's, 10-2000 Hz. 12 hours |
| Durability | 500 cycles of mating and unmating, 500 CPH max. |
| Moisture Resistance | Insulator resistance > 100 megohms |
| SaltSpray | 48 hours |