



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Header**

PCB Mount Orientation: **Vertical**

Connector System: **Board-to-Board**

Number of Positions: **20**

Number of Rows: **2**

Features

Product Type Features

PCB Connector Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Breakaway
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Connector Contact Load Condition	Fully Loaded
Board-to-Board Configuration	Parallel
PCB Mount Orientation	Vertical
Number of Positions	20
Number of Rows	2

Electrical Characteristics

Insulation Resistance	5000 MΩ
Dielectric Withstanding Voltage (Max)	750 Vrms

Body Features

Primary Product Color	Green
-----------------------	-------

Contact Features



Contact Underplating Material	Nickel
Contact Mating Area Plating Material Thickness	.8 µm[31.5 µin]
Mating Square Post Dimension	.63 mm[.025 in]
PCB Contact Termination Area Plating Material Thickness	3 µm
Contact Shape & Form	Square
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Mating Area Plating Material	Gold (Au), Gold Flash
Contact Type	Pin
Contact Current Rating (Max)	5 A

Termination Features

Termination Post & Tail Length	3.2 mm[.126 in]
Square Termination Post & Tail Dimension	.63 mm[.025 in]
Termination Method to PCB	Through Hole - Solder

Mechanical Attachment

PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Mating Alignment	Without

Housing Features

Housing Material	PBT
Centerline (Pitch)	2.54 mm[.1 in]

Dimensions

Row-to-Row Spacing	2.54 mm[.1 in]
PCB Thickness (Recommended)	1.57 mm[.062 in]

Usage Conditions

Housing Temperature Rating	Standard
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------



Packaging Features

Packaging Quantity	400
Packaging Method	Box, Carton

Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C


Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts




TE Part # 1-215309-0
2X10P HV100 REC CON. TE, 8.5MM




TE Part # 6-534236-0
20 MODII VRT DR CE 100/120



TE Part # 146219-3
20 MODIV VRT DR CE 100/125




TE Part # 1-215307-0
2X10P HV100 REC CON. TE, 7.0MM



TE Part # 1-925367-0
MOD 4 REC.HSG 2X10P




TE Part # 1-969973-0
2x10P HV100 REC. CON, SMD, GOLD, BLISTER




TE Part # 2-534236-4
48 MODII VRT DR CE 100/120




TE Part # 2-215307-1
2X21P HV100 REC CON. TE, 7.0MM




TE Part # 1-534236-0
20 MODII VRT DR CE 100/120




TE Part # 3-534236-0
60 MODII VRT DR CE 100/120




TE Part # 2-1017008-9
58 MODII VRT DR CE HI TEMP




TE Part # 2-534236-7
54 MODII VRT DR CE 100/120



TE Part # 2-534236-2
44 MODII VRT DR CE 100/120



TE Part # 1-829264-0
2X10P HV100 REC.CON.B/TE,6.2MM, NO KINK




TE Part # 1-216604-0
2X10P HV190FEDERLEI

Also in the Series | AMPMODU Headers



Automotive Headers(1)




Board-to-Board Headers & Receptacles(1576)



Connector Contacts(47)



Connector Hardware(1)




PCB Headers & Receptacles(1621)



Rectangular Power Connectors(43)




Wire-to-Board Connector Assemblies & Housings(5)




Wire-to-Board Headers & Receptacles (114)


Customers Also Bought




TE Part #1-215307-0
2X10P HV100 REC CON. TE, 7.0MM



TE Part #3-1761606-5
IDC LOW PRO HDR 50P VERT LA



TE Part #5103311-1
A/L LOW PRO HDR 10P RA BLACK



TE Part #3-643814-3
03P MTA100 CONN ASSY POL RIB




TE Part #2-338309-2
9P.HDP20 PLUG ASSY



TE Part #2-338313-2
9P.HDP20 REC. ASSY




TE Part #207684-3
AMPLIMITE,SKT CONT,SZ 22



TE Part #292161-4
CT P/HDR ASSY V 4P W/KINK NAT



TE Part #5226993-1
VERTICAL JACK, BNC PCB



TE Part #22987-4
SCREW,SELF TAPPING,PAN HD

Documents

Product Drawings
10P AMPMODU II PIN HDR.

English

CAD Files
3D PDF

3D

Customer View Model
ENG_CVM_CVM_1-826632-0_R.2d_dxf.zip

English

Customer View Model
ENG_CVM_CVM_1-826632-0_R.3d_igs.zip

English

Customer View Model
ENG_CVM_CVM_1-826632-0_R.3d_stp.zip

English

By downloading the CAD file I accept and agree to the Terms and Conditions of use.

Agency Approvals

1-826632-0

PCB Mount Header, Vertical, Board-to-Board, 20 Position, 2.54 mm [.1 in] Centerline, Breakaway, Gold (Au) / Gold Flash, AMPMODU Headers



[UL Report](#)

English