

2334570-8 ✓ ACTIVE

MULTI-BEAM


TE Internal #: 2334570-8

PCB Mount Receptacle, Right Angle, Board-to-Board, 32 Position,
2.54 mm / 5.5 mm [.1 in / .216 in] Centerline, Fully Shrouded, Gold
(Au)

[View on TE.com >](#)



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Type: **PCB Mount Receptacle**

PCB Mount Orientation: **Right Angle**

Connector System: **Board-to-Board**

Number of Positions: **32**

Number of Rows: **5**

Features

Product Type Features

Mixed & Hybrid Header	Yes
Connector Shape	Rectangular
PCB Connector Type	PCB Mount Receptacle
Connector System	Board-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Columns	12
Number of Loaded Positions	32
Number of Signal Positions	25
Number of Power Positions	7
PCB Mount Orientation	Right Angle



Number of Positions	32
---------------------	----

Number of Rows	5
----------------	---

Electrical Characteristics

Operating Voltage	60 VDC, 400 VDC
-------------------	-----------------

Body Features

Primary Product Color	Black
-----------------------	-------

Contact Features

Contact Underplating Material	Nickel
-------------------------------	--------

Contact Underplating Material Thickness	1.27 – 2.54 μm [50 – 100 μin]
---	--

Contact Mating Area Plating Material Thickness	.381 μm [15 μin]
--	---

PCB Contact Termination Area Plating Material Thickness	2.54 – 5.08 μm [100 – 200 μin]
---	---

Contact Layout	Matrix
----------------	--------

Contact Base Material	Copper Alloy
-----------------------	--------------

PCB Contact Termination Area Plating Material	Tin
---	-----

Contact Mating Area Plating Material	Gold (Au)
--------------------------------------	-----------

Contact Type	Receptacle
--------------	------------

Contact Current Rating (Max)	100 A
------------------------------	-------

Termination Features

Termination Post & Tail Length	2.54 mm[.1 in]
--------------------------------	----------------

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

Mating Retention	Without
------------------	---------

PCB Mount Retention Type	Hold-Down
--------------------------	-----------

PCB Mount Alignment Type	Hold-Down
--------------------------	-----------

PCB Mount Retention	With
---------------------	------

PCB Mount Alignment	With
---------------------	------

Connector Mounting Type	Board Mount
-------------------------	-------------

Mating Alignment	Without
------------------	---------

Housing Features

Housing Material	High Temperature Thermoplastic Glass-Filled
------------------	---

Centerline (Pitch)	2.54 mm, 5.5 mm[.1 in][.216 in]
--------------------	---------------------------------



Dimensions

Row-to-Row Spacing	2 mm[.07 in]
Connector Length	61 mm[2.4 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]

Operation/Application

Circuit Application	Power & Signal
---------------------	----------------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	44
Packaging Method	Tray

Product Compliance

[For compliance documentation, visit the product page on TE.com>](#)


EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JUNE 2024 (241) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Reflow solder capable to 245°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on

requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 6450830-1
MBXL R/A HDR 2LP + 8S + 2LP


Customers Also Bought



TE Part #1658621-4
20 NOVO MIL/CTR 15DP, LEAD FREE



TE Part #2334571-1
MBPLUS R/A RCPT 20S + 6P



TE Part #1-2334530-2
MBPLUS, R/A, PLUG, SOLDER, 5LP + 25S + 2P

Documents

Product Drawings

[MBPLUS, R/A, REC., SOLDER, 5LP + 25S + 2P](#)

English

CAD Files

Customer View Model

[ENG_CVM_CVM_2334570-8_A.3d_stp.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2334570-8_A.2d_dxf.zip](#)

English

Customer View Model

[ENG_CVM_CVM_2334570-8_A.3d_igs.zip](#)

English

[3D PDF](#)

3D

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Product Specifications

[Application Specification](#)

English

2334570-8

PCB Mount Receptacle, Right Angle, Board-to-Board, 32 Position, 2.54 mm / 5.5 mm [.1 in / .216 in] Centerline, Fully Shrouded, Gold (Au)

