



AMP-LATCH | AMP-LATCH Universal Headers

TE Internal #: 5499206-8
Wire-to-Board, 34 Position, 2.54 mm [.1 in] Centerline, Vertical,
Through Hole - Solder, 2 Row, AMP-LATCH Universal Headers,
Ribbon Cable Connectors

[View on TE.com >](#)

Connectors > PCB Connectors > Wire-to-Board Connectors > FFC, FPC & Ribbon Connectors > Ribbon Cable Connectors >
AMP-LATCH UNIVERSAL HEADERS



Connector System: **Wire-to-Board**
Number of Positions: **34**
Centerline (Pitch): **2.54 mm [.1 in]**
PCB Mount Retention: **Without**
PCB Mount Orientation: **Vertical**

[All AMP-LATCH UNIVERSAL HEADERS \(523\)](#)

Features

Product Type Features

Connector Product Type	Connector Assembly
Connector Mating Latch & Lock Type	Long
Ribbon Cable Connector Header Type	Universal Ejection Pin Headers
Connector System	Wire-to-Board
Connector & Housing Type	Plug
Connector & Contact Terminates To	Printed Circuit Board

Configuration Features

Number of Positions	34
PCB Mount Orientation	Vertical
Number of Rows	2

Electrical Characteristics

Operating Voltage	250 VAC
-------------------	---------



Insulation Resistance	5000 MΩ
Body Features	
Primary Product Color	Black
Connector Profile	Standard
Contact Features	
Contact Mating Area Plating Material Thickness	.76 μm[30 μin]
Mating Square Post Dimension	.64 mm[.025 in]
Contact Shape & Form	Square
PCB Contact Termination Area Plating Material Thickness	2.54 μm[100 μin]
Contact Mating Area Plating Material	Gold (Au)
Contact Base Material	Phosphor Bronze
PCB Contact Termination Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	1 A
Termination Features	
Termination Post & Tail Diameter	.64 mm[.025 in]
Termination Post & Tail Length	2.79 mm[.11 in]
Termination Method to PCB	Through Hole - Solder
Mechanical Attachment	
Panel Mount Feature	Without
Mating Alignment	With
PCB Mount Alignment	Without
PCB Mount Retention	Without
Mating Alignment Type	Center, Dual Polarizing Bar
Mating Retention	With
Mating Retention Type	Ejection Latch
Connector Mounting Type	Board Mount
Housing Features	
Housing Material	Glass-Filled Nylon/Polyester
Centerline (Pitch)	2.54 mm[.1 in]
Dimensions	
Shrouded End Dimension	3.81 mm[.15 in]



PCB Thickness (Recommended)	1.57 mm[.062 in]
Connector Height	13.94 mm[.548 in]
Connector Length	62.48 mm[2.46 in]
Row-to-Row Spacing	2.54 mm[.1 in]

Usage Conditions

Housing Temperature Rating	Standard
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

Packaging Features

Packaging Quantity	18
Packaging Method	Tray

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides



on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) ‘Guidance on requirements for substances in articles’ posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts

TE Part # 1658621-8
34 NOVO MIL/CTR 15DP,LEAD FREE

TE Part # 1658623-8
34 NOVO MIL 30DP, LEAD FREE

TE Part # 499252-6
034 STRAIN RELIEF A-L RCPT

TE Part # 1-1658526-9
609-3441LF FEM SOCKET,LEAD FREE

TE Part # 2-1658527-8
622-3441LF=FSKT IDC S 34 30AU

TE Part # 1658624-8
034 NOVO DUAL 30DP FT

TE Part # 3-1437021-2
609-3431HD=FSKT IDC S 34 SR

TE Part # 1658620-8
34 NOVO MIL 15DP, LEAD FREE

TE Part # 1658622-8
34 NOVO MIL/CTR 30DP,LEAD FREE

TE Part # 102320-1
UNIVERSAL HEADER LATCH

TE Part # 1-1658526-8
609-3430LF FEM SOCKET,LEAD FREE

Also in the Series | AMP-LATCH Universal Headers

Connector Hardware(13)

Ribbon Cable Connectors(523)

Customers Also Bought



TE Part #643430-1
15P UMNL HDR ASSY POL 94VO

TE Part #20003318-00
PRESS XDCR M32JM-00000E-010BG

TE Part #643405-1
05P UMNL PIN HDR ASSY POL NATL

TE Part #1-794106-0
20P MINI UMNL R/A HDR ASSY

TE Part #1474678-7
FSK-12.5KJ-36

TE Part #641975-1
15P UMNL PIN HDR ASSY POL NATL

TE Part #5102321-8
A/L UNIV HDR 34P VERT LAT

TE Part #6646597-1
278-0933-10200A=CONN,SKT

TE Part #1-66473-9
SKT,.062 DIA,.045 SQ POST,LP

TE Part #1-1586041-4
14P VAL-U-LOK R/A HDR V2

Documents

Product Drawings

A/L UNIV HDR 34P VERT LAT

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5499206-8_C.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_5499206-8_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5499206-8_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages



Ribbon Cable Interconnect Solutions

English

Product Specifications

Product Specification

English