




Connectors > PCB Connectors > PCB Headers & Receptacles > SUPERSEAL Connector Headers: 1.0 mm



PCB Connector Type: PCB Mount Header

PCB Mount Orientation: Right Angle

Connector System: Wire-to-Board

Number of Positions: 26

Number of Rows: 4

[All SUPERSEAL Connector Headers: 1.0 mm \(39\)](#)

Features

Product Type Features

Connector Shape	Rectangular
PCB Connector Type	PCB Mount Header
Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	Yes
Connector & Contact Terminates To	Printed Circuit Board
Connector Product Type	Connector Assembly

Configuration Features

Number of Signal Positions	26
PCB Mount Orientation	Right Angle
Number of Positions	26
Number of Rows	4

Electrical Characteristics



Voltage Rating (Max)	250 VDC
----------------------	---------

Body Features

Connector & Keying Code	4
Primary Product Color	Black

Contact Features

Mating Pin Diameter	1 mm[.039 in]
Contact Size	1mm
Contact Mating Area Plating Material	Gold (Au)
Contact Type	Pin
Contact Current Rating (Max)	7 A

Termination Features

Termination Method to PCB	Through Hole - Solder
---------------------------	-----------------------

Mechanical Attachment

PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Mating Alignment	With

Housing Features

Centerline (Pitch)	3 mm[.118 in]
--------------------	---------------

Dimensions

Connector Width	36.5 mm[1.44 in]
Connector Length	39.5 mm[1.55 in]

Usage Conditions

Operating Temperature (Max)	125 °C[257 °F]
Operating Temperature Range	-40 – 125 °C[-40 – 257 °F]

Operation/Application

Circuit Application	Signal
---------------------	--------

Packaging Features

Packaging Quantity	16
Packaging Method	Tube



Product Compliance


For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JAN 2025 (247) Candidate List Declared Against: JAN 2025 (247) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 240°C

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: <https://echa.europa.eu/guidance-documents/guidance-on-reach>

Compatible Parts



TE Part # 1746107-5
SUPER SEAL 26POS CAP SUB ASSY H AU



TE Part # 1473416-1
SUPER SEAL 26POS PLUG ASSY




TE Part # 9-6437287-9
SUPER SEAL 26POS CAP ASSY H AU


Also in the Series | **SUPERSEAL 1.0mm**



Automotive Housings(22)



Automotive Terminals(10)



PCB Headers & Receptacles(39)



Rectangular Backshells & Clamps(3)

Customers Also Bought



TE Part #348461-1
ECON 3 LC PLUG SILIC



TE Part #CAT-SU763-CH8172
SUPERSEAL Connector Housings: 1.0 mm



TE Part #CAT-SU763-H342
SUPERSEAL Connector Headers: 1.0 mm

Documents

Product Drawings

SUPER SEAL 26POS CAP ASSY H AU

Japanese

SUPER SEAL 26POS CAP ASSY H AU

English

CAD Files

Customer View Model

ENG_CVM_CVM_6473423-1_C.2d_dxf.zip

English

3D PDF

3D

Customer View Model

ENG_CVM_CVM_6473423-1_C.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_6473423-1_C.3d_stp.zip

English

By downloading the CAD file I accept and agree to the [Terms and Conditions](#) of use.

Datasheets & Catalog Pages

CONNECTOR SELECTOR

English

Product Specifications

Application Specification



English

Super Seal Connector

Japanese

Application Specification

Japanese

Instruction Sheets

Instruction Sheet (non U.S.)

English

SUPER SEAL CONNECTOR PLUG HOUSING CONNECTOR

English

Agency Approvals

UL Report

English